

TFS_330/J/VF2209

碱度：2.4

相当规格

GB/T

36037 S AAF 2 DC

141/4 SAAF 2 DC

特性与用途

--- 新编连续剧与综艺大联欢 从深圳到上海全记录 ---

测试	0.03	0.163	0.55	0.031	0.011	330	8.82	2.16
----	------	-------	------	-------	-------	-----	------	------

[illegible][illegible]

熔敷金属化学成分(质量分数,%)

© 2006 The Authors
Journal compilation © 2006 Blackwell Publishing Ltd

				CPU	AWS A5.39		C	MH	SI	P	S	C
--	--	--	--	-----	-----------	--	---	----	----	---	---	---

GB/T 标准 0.04 120

2017年12月15日 星期五

Downloaded from <http://www.sagepub.com> at NANYANG TECH UNIV LIBRARY on June 11, 2015

Diagram illustrating the cross-section of a composite material structure, showing multiple layers and internal features. The structure is labeled with various numbers and letters, indicating different components and layers.

[illegible]

Category	18-24	25-34	35-44	45-54	55-64	65+
Total	15	25	30	20	10	0
Male	10	20	25	15	10	0
Female	20	30	35	25	15	0
Male	10	20	25	15	10	0
Female	20	30	35	25	15	0

[illegible]

100

Figure 6. The effect of the number of iterations on the accuracy of the proposed algorithm. The results are averaged over 10 trials.

Figure 1. The effect of the number of trials on the number of correct responses. The number of correct responses was significantly higher than the number of incorrect responses in all cases. Error bars represent the standard error of the mean.